



QUICK-LOCK FLEX DN 200 - DN 800

Quick-Lock FLEX DN	seal DN	sleeve-length	total diameter rolled (with seal)	Suitable for pipes from / to		Stainless steel sleeve			seal			max. radial offset size	Installation packer	seal thickness incl. seal nubs	Total weight (sleeve with seal)
				Pipe ID min.	Pipe ID max.	Wall thickness	1.4404 Pipe rolled	max. expanded diameter	seal thickness	Height of seals	Sealed area (single installation)				
mm DN	mm	mm L	mm Dg	mm DN min	mm DN max	mm S 1.4404	mm da	mm DA	mm S seal	mm Hn	mm AE	mm bis zu	mm VP	mm	kg
200	200	360	173	196	207	1,2	159	202	2,0	5,0	320	20	VP 150-200 VFWL	7,0	2,47
250	250	360	215	247	261	1,2	199	252	2,0	6,0	315	20	VP 200-300 VFWL	8,0	3,13
300	300	360	252	293	313	1,2	234	300	2,0	7,0	310	25	VP 200-300 VFWL	9,0	3,71
380	350	360	322	367	386	1,5	304	377	2,0	7,0	310	25	VP 350-500 VFWL	9,0	5,30
400	400	360	347	390	415	1,5	327	405	2,0	8,0	310	25	VP 350-500 VFWL	10,0	5,75
450	450	360	387	438	464	2,0	367	455	2,0	8,0	395	25	VP 350-500 VFWL	10,0	11,10
500	500	460	450	487	515	2,0	428	505	2,0	9,0	385	25	VP 350-500 VFWL / VP 500-600 VFWL	11,0	12,15
600	600	460	542	582	617	2,0	519	607	2,5	9,0	390	25	VP 500-600 VFWL	11,5	14,80
700	700	460	593	675	725	2,0	570	709	2,5	9,0	375	25	VP 600-800 VFWL	11,5	17,80
800	700	460	597	760	804	2,0	574	818	2,5	9,0	375	25	VP 600-800 VFWL	11,5	21,60