



QUICK-LOCK MINI DN 100 - DN 150

Quick-Lock MINI DN	EPDM seal DN	sleeve-length	total diameter rolled with seal)	Suitable for pipes from / to		Stainless steel sleeve			seal			Installation packer	seal-thickness	Total weight (sleeve with seal)
				Pipe ID min.	Pipe ID max.	Wall-thickness	1.4404 Pipe rolled	max. expanded diameter	seal-thickness	Height of seals	Sealed area (single installation)			
mm DN	mm	mm L	mm Dg	mm DN min	mm DN max	mm S 1.4404	mm da	mm DA	mm S seal	mm Hn	mm AE	VP	mm	kg
100 - 90 ^{1 3}	100 - 90	90	96	91	105	0,6	85	100	1,5	4,0	52 ¹	VP 100-150 VFW / VP 100-125 Bogen	5,5	0,25
100 - 145 ²	100 - 145	145	96	91	105	0,6	85	100	1,5	4,0	100	VP 100 - 150 VFW	5,5	0,37
125 - 90 ^{1 3}	125 - 90	90	101	101	126	0,6	90	118	1,5	4,0	52 ¹	VP 100-150 VFW / VP 100-125 Bogen	5,5	0,28
125 - 145 ²	125 - 145	145	100	101	126	0,6	89	118	1,5	4,0	100	VP 100 - 150 VFW	5,5	0,40
150 - 90 ^{1 3}	150 - 90	90	132	147	155	0,6	120	146	2,0	4,0	52 ¹	VP 100-150 VFW / VP 100-125 Bogen	6,0	0,43
150 - 145 ²	150 - 145	145	132	147	155	0,6	120	146	2,0	4,0	100	VP 100 - 150 VFW	6,0	0,66

¹ Sleeve can be used in bended pipes (bends up to 45°).

² Sleeve can only be used in straight pipes.

³ seal must be shortened.

All sleeves are only produced with double flaring.